

Jeremias Model DWKL and SWKL


THE CONICAL JOINT - Intelligent Design

Jeremias, Inc., Marietta, GA



Jeremias Model DWKL and SWKL


- Cutaway view of the joints after joining
 - DWKL double wall
 - SWKL single wall
- Conical joint design, high pressure capable (90" WC), no silicone sealant (steel to steel)
 2.2" of surface area at each joint





Jeremias Model DWKL and SWKL

- Close up view of the joints before joining
 - DWKL double wall
 - SWKL single wall
- Conical joint design, high pressure capable (90" WC), no silicone sealant (steel to steel)









Jeremias Model DWKL and SWKL

Assembly of the **DWKL** double wall.

Male end

Female end










Jeremias Model DWKL and SWKL

Assembly of the **DWKL** double wall.





Male end

Female end

A Closeup Cross-section of the Jeremias Model DWKL shows the male and female ends of the conical joint design after assembly.





Competitor-Comparison

Our Competition- Flange to Flange



½" Rolled flanges



Step 1 Fill Inner Vee Band (OVB) with proper sealant.



Step 2 Position Inner OVB below flange of pipe or fitting.



Cut

Fingers?

Step 3 Mate flanges of two pipes. Position Inner OVB over both flanges and tighten.



Step 4 Position Outer Channel Band around outer casing. Align with pipe grooves and tighten.



Competitors vs. Jeremias Comparison

Our Competition- Flange to Flange



Jeremias- the Conical Joint





Competitors vs. Jeremias Conclusion

Reasons why Jeremias is better

- 1. The best response time for quotes, sizings, CAD drawings and calculations- usually same day for quotes
- 2. The best lead times for shipping- normally 5 to 10 business days standard
- 3. The best pricing structure in the industry to our reps
- 4. Truly professional Customer Service- reliable and friendly
- 5. The ingenious German Conical joint design- No silicon sealant, No gaskets, No leaks
- 6. Made in the USA
- 7. All UL Listed
- 8. The highest UL Listed pressure rating of 90" W.C.- we test stronger
- 9. The highest UL Listed temperature prior to pressure rating of 1400° F we test higher
- 10. The only standard ALL Stainless Steel, including accessories, system on the market- NO rust
- 11. The only system with no steel bridges between inner liner and outer jacket- less heat transfer- No hot spots
- 12. The largest steel-to-steel surface area at joint connection- 4 times that of competitor's ½" rolled flanges
- 13. The smallest footprint in the industry due to best UL clearance to combustibles
- 14. The best warranty in the industry, 25 year factory warranty
- 15. The most beautiful finished chimney stack you will ever see
- 16. Forward thinking company- still inventing and creating, improving every day